

ARIES

ARSENIC REMOVAL

ARSENIC REMOVAL

PRO SERIES, SINGLE-BED, DROP-IN CARTRIDGE

Aries arsenic removal cartridges utilize the advanced media technology of ResinTech® ASM-10-HP, an arsenic selective media with unsurpassed arsenic capacity. ASM-10-HP is a strongly basic hybrid anion exchange resin that is effective over the entire pH range of potable water. Sized to fit standard slimline and big blue housings.



HIGHLIGHTS

- Highest Capacity Arsenic Removal
- Resintech® ASM-10-HP
- Fits Standard Residential & Industrial Size Housing
- Oversized Cartridge for Maximum Media Fill
- Lot numbered
- Made in the USA

APPLICATIONS

- Drinking Water
- Food and Beverage Industry
- Light Commercial

MEDIA

- ResinTech® ASM-10-HP (100%)

CERTIFICATIONS

- WQA Gold Seal
- California Prop. 65 Compliant

SPECIFICATIONS

- Nominal Rating of 25µ
- Max Pressure of 125 psi (861.85 kpa)
- Max Temperature 100°F (37.8 °C)

DIMENSIONS	SERVICE FLOW	MAX FLOW	CAPACITY	PART NUMBER
2.5 x 10 in. (Slim Line)	.25 gpm (.95 lpm)	.50 gpm (1.89 lpm)	1,000 gallons (3785 liters)	AF-10-3695
2.5 x 20 in. (Slim Line)	.50 gpm (1.89 lpm)	1.0 gpm (3.79 lpm)	4,000 gallons (15,142 liters)	AF-20-3695
4.5 x 10 in. (Super Blue)	.50 gpm (1.89 lpm)	1.0 gpm (3.79 lpm)	4,500 gallons (17,034 liters)	AF-10-3695-BB
4.5 x 20 in. (Super Blue)	1.0 gpm (3.79 lpm)	2.0 gpm (7.57 lpm)	9,000 gallons (34,069 liters)	AF-20-3695-BB



COMPONENT

Filter cartridge Certified to NSF/ANSI Standard 42 and NSF/ANSI Standard 61 for material requirement(s) only. Filter cartridge Certified to NSF/ANSI Standard 372 for low lead compliance.

Revision 1.0

© 2020 ResinTech, Inc.

