BITUMINOUS CARBON

PRO SERIES, SINGLE BED, DROP-IN CARTRIDGE

TASTE & ODOR CORRECTION
CHLORINE REMOVAL
ORGANICS REMOVAL

Aries General Purpose Acid Washed Bituminous Carbon cartridges are an ideal choice for taste and odor control, chlorine removal, and organic reduction. Carbon filtration is an inexpensive and effective way to remove chemicals and contaminants commonly found in tap water. ResinTech® coconut shell carbons are acid washed for a balanced pH. Sized to fit standard slimline and big blue housings.



HIGHLIGHTS

- Fits standard residential & industrial housings
- Optimum mesh size for greater adsorption
- Acid washed ensures a neutral pH
- Up to 50% higher capacity for longer life
- Lot numbered
- Made in the USA
- Virtually Dust-free

APPLICATIONS

- _
- •

MEDIA

- ResinTech® AGC-AW (100%)*
- * Mesh varies by cartridge dimensions.

CERTIFICATIONS

- WQA Gold Seal
- California Prop. 65 Compliant

SPECIFICATIONS

- Nominal Rating of 25µ
- Max Pressure of 125 psi (861.85 kpa)
- Max Temperature 100 °F (37.8 °C)

DIMENSIONS	SERVICE FLOW	MAX FLOW	CAPACTIY	PART NUMBER
2.5 x 10 in. (Slim Line)	0.75 gpm (2.84 lpm)	1 gpm (3.79 lpm)	4,000 gallons (15,142 liters)	AF-10-1051
2.5 x 20 in. (Slim Line)	1 gpm (3.79 lpm)	2 gpm (7.57 lpm)	9,000 gallons (34,069 liters)	AF-20-1051
4.5 x 10 in. (Super Blue)	2 gpm (7.57 lpm)	4 gpm (15.14 lpm)	13,000 gallons (49,210 liters)	AF-10-1041-BB
4.5 x 20 in. (Super Blue)	3 gpm (11.36 lpm)	5 gpm (18.93 lpm)	30,000 gallons (113,562 liters)	AF-20-1041-BB



COMPONENT

Filter cartridge Certified to NSF/ANSI Standard 42 and NSF/ANSI Standard 61 for material requirement(s) only. Filter cartridge Certified to NSF/ANSI Standard 372 for low lead compliance.

Revision 1.0 © 2020 ResinTech, Inc.

