

# ARIES CARTRIDGE SPECIFICATION SHEET

## ARIES CALCOR & CARBON

PRO SERIES, LAYERED BED, DROP-IN CARTRIDGE

**TASTE & ODOR CORRECTION**  
**CHLORINE REMOVAL**  
**ORGANICS REMOVAL**  
**PH NEUTRALIZATION**

Aries GAC/Calcor Cartridges contain Acid-washed Coconut Shell carbon along with unique a blend of Calcite® and Corosex®. The unique combination of media ensure for the correction of taste, odor, and chlorine over a wider pH range thereby ensuring a more consistently balanced effluent without the negative impact of over correction. Sized to fit standard slimline and big blue housings.



### HIGHLIGHTS

- Fits Standard Residential & Industrial Size Housing
- Oversized Cartridge for Maximum Media Fill
- Lot numbered
- Made in the USA

### APPLICATIONS

- Drinking Water
- Post RO POU
- POE Whole House
- Light Commercial

### MEDIA

- AGC-CS-AW (30%)\*
- Calcor (70%)

\* Mesh varies by cartridge dimensions.

### CERTIFICATIONS

- WQA Gold Seal
- California Prop. 65 Compliant

### SPECIFICATIONS

- Nominal Rating of 25µ
- Max Pressure of 125 psi (861.85 kpa)
- Max Temperature 100 °F (37.8 °C)

DIMENSIONS	SERVICE FLOW	MAX FLOW	CAPACITY	PART NUMBER
2.5 x 10 in. (Slim Line)	.5 gpm (1.89 lpm)	1 gpm (3.79 lpm)	2,500 gallons (9,464 liters)	<b>AF-10-4210</b>
2.5 x 20 in. (Slim Line)	1 gpm (3.79 lpm)	2 gpm (7.57 lpm)	4,300 gallons (16,277 liters)	<b>AF-20-4210</b>
4.5 x 10 in. (Super Blue)	2 gpm (7.57 lpm)	3 gpm (11.36 lpm)	5,000 gallons (18,927 liters)	<b>AF-10-4210-BB</b>
4.5 x 20 in. (Super Blue)	3 gpm (11.36 lpm)	5 gpm (18.93 lpm)	12,000 gallons (45,425 liters)	<b>AF-20-4210-BB</b>



### COMPONENT

Filter cartridge Certified to NSF/ANSI Standard 42 and NSF/ANSI Standard 61 for material requirement(s) only. Filter cartridge Certified to NSF/ANSI Standard 372 for low lead compliance.

Revision 1.0

© 2020 ResinTech, Inc.

