CALCOR + pH NEUTRALIZATION

PRO SERIES, SINGLE-BED, DROP-IN CARTRIDGE

PH NEUTRALIZATION
MINERALIZATION
CORROSION CONTROL

Aries Calcor Cartridges contain a unique a blend of Calcite® and Corosex®. The unique combination of media ensure pH correction over a wider range thereby ensuring a more consistently balanced effluent without the negative impact of over correction. Sized to fit standard slimline and big blue housings.



HIGHLIGHTS

- Fits Standard Residential & Industrial Size Housing
- Oversized Cartridge for Maximum Media Fill
- Lot numbered
- Made in the USA

APPLICATIONS

- Drinking Water
- Post RO
- POU
- POE Whole House
- Light Commercial

MEDIA

• Calcor (100%)

CERTIFICATIONS

- WQA Gold Seal
- California Prop. 65 Compliant

SPECIFICATIONS

- Nominal Rating of 25µ
- Max Pressure of 125 psi (861.85 kpa)
- Max Temperature 100°F (37.8 °C)

DIMENSIONS	SERVICE FLOW	MAX FLOW	CAPACITY	PART NUMBER
2.5 x 10 in. (Slim Line)	0.5 gpm (1.89 lpm)	1 gpm (3.79 lpm)	3,750 gallons (14,195 liters)	AF-10-3232
2.5 x 20 in. (Slim Line)	1 gpm (3.79 lpm)	2 gpm (7.57 lpm)	13,000 gallons (49,210 liters)	AF-20-3232
4.5 x 10 in. (Super Blue)	1.5 gpm (5.68 lpm)	3 gpm (11.36 lpm)	15,000 gallons (56,781 liters)	AF-10-3232-BB
4.5 x 20 in. (Super Blue)	3 gpm (11.36 lpm)	5 gpm (18.93 lpm)	36,000 gallons (136,275 liters)	AF-20-3232-BB



COMPONENT

Filter cartridge Certified to NSF/ANSI Standard 42 and NSF/ANSI Standard 61 for material requirement(s) only. Filter cartridge Certified to NSF/ANSI Standard 372 for low lead compliance.

Revision 1.0 © 2020 ResinTech, Inc.

