

ARIES CARBON & PHOSPHATE

PRO SERIES, LAYERED BED, DROP-IN CARTRIDGE

TASTE & ODOR CORRECTION
ORGANICS REMOVAL
CHLORINE REDUCTION
SCALE & CORROSION INHIBITOR

Aries Carbon/Phosphate cartridges use the combination of phosphate crystals and activated carbon to inhibit scale buildup while simultaneously addressing chlorine, taste and odor (CTO) concerns. The carbon dramatically improves the aesthetic quality of drinking water, while the phosphate works to sequester iron, manganese, & calcium and protecting metal parts from scale & corrosion. Sized to fit standard slimline and big blue housings.



HIGHLIGHTS

- Fits Standard Residential & Industrial Size Housing
- Oversized Cartridge for Maximum Media Fill
- Lot numbered
- Made in the USA

APPLICATIONS

- Light Commercial
- Water heaters
- Food service, Coffee & Vending/Ice Machines
- RO pretreatment

MEDIA

- AGC-CS-AW (50%)*
- Slow Melt Phosphate Crystals (50%)

* Mesh varies by cartridge dimensions.

CERTIFICATIONS

- WQA Gold Seal
- California Prop. 65 Compliant

SPECIFICATIONS

- Nominal Rating of 25µ
- Max Pressure of 125 psi (861.85 kpa)
- Max Temperature 100 °F (37.8 °C)

| DIMENSIONS | SERVICE FLOW | MAX FLOW | CAPACITY | PART NUMBER |
|---------------------------|---------------------|----------|------------|----------------------|
| 2.5 x 10 in. (Slim Line) | 1.0 gpm (3.79 lpm) | - | 2,500 ppm | AF-10-3302 |
| 2.5 x 10 in. (Slim Line) | 1.0 gpm (3.79 lpm) | - | 5,000 ppm | AF-10-3305 |
| 2.5 x 20 in. (Slim Line) | 2.0 gpm (7.57 lpm) | - | 10,000 ppm | AF-20-3310 |
| 2.5 x 20 in. (Slim Line) | 2.0 gpm (7.57 lpm) | - | 20,000 ppm | AF-20-3312 |
| 4.5 x 10 in. (Super Blue) | 3.0 gpm (11.36 lpm) | - | 10,000 ppm | AF-10-3311-BB |
| 4.5 x 10 in. (Super Blue) | 3.0 gpm (11.36 lpm) | - | 20,000 ppm | AF-10-3312-BB |
| 4.5 x 20 in. (Super Blue) | 5.0 gpm (18.93 lpm) | - | 20,000 ppm | AF-20-3312-BB |
| 4.5 x 20 in. (Super Blue) | 5.0 gpm (18.93 lpm) | - | 40,000 ppm | AF-20-3314-BB |



COMPONENT

Filter cartridge Certified to NSF/ANSI Standard 42 and NSF/ANSI Standard 61 for material requirement(s) only. Filter cartridge Certified to NSF/ANSI Standard 372 for low lead compliance.

Revision 1.0

© 2020 ResinTech, Inc.

