ARIES CARTRIDGE SPECIFICATION SHEET

CATALYTIC CARBON

PRO SERIES, SINGLE BED, DROP-IN CARTRIDGE

TASTE & ODOR CORRECTION
CHLORAMINE REMOVAL
HYDROGEN SULFIDE REMOVAL
ORGANICS REMOVAL

Aries Catalytic Carbon cartridge contains Calgon Centaur™ Carbon. This is a specially enhanced carbon developed through an advanced process starting as Granular Activated Carbon (GAC). By altering the electron structure of GAC, it enhances its catalytic capability beyond traditional carbons. Sized to fit standard slimline and big blue housings."

APPLICATIONS

- Drinking Water
- Post RO
- Light Commercial

MEDIA

Calgon Centaur[™] (100%)

SPECIFICATIONS

- Nominal Rating of 25µ
- Max Pressure of 125 psi (861.85 kpa)
- Max Temperature 100 °F (37.8 °C)



HIGHLIGHTS

- Acheives a Wider Range of Catalysis
- Reduces Reliance on Additional Chemical Treatment
- Fits Standard Residential & Industrial Size Housing
- Oversized Cartridge for Maximum Media Fill
- Lot numbered
- Made in the USA

DIMENSIONS	SERVICE FLOW	MAX FLOW	CAPACTIY	PART NUMBER
2.5 x 10 in. (Slim Line)	.50 gpm (1.89 lpm)	1.0 gpm (3.79 lpm)	2,000 gallons (7,571 liters)	AF-10-1053
2.5 x 20 in. (Slim Line)	.75 gpm (2.84 lpm)	2.0 gpm (7.57 lpm)	3,500 gallons (13,249 liters)	AF-20-1053
4.5 x 10 in. (Super Blue)	1.0 gpm (3.79 lpm)	2.0 gpm (7.57 lpm)	4,375 gallons (16,561 liters)	AF-10-1042-BB
4.5 x 20 in. (Super Blue)	1.5 gpm (5.68 lpm)	3.0 gpm (11.36 lpm)	8,750 gallons (33,122 liters)	AF-20-1042-BB



