


VP-17-4210

(Organics Removal- Dual Bed Cartridge)

Effective date 1 January 2021

SECTION 1: Identification	
1A: Product Names	VP-17-4210
1B: Common Name	Organics Removal- Dual Bed Cartridge (SBACR-MP- HP Resin, AGC-50-AW Carbon)
1C: Intended use	Organic traps and other exchanges where an acrylic strong base anion resin is desired.
1D: Manufacturer Address	ResinTech, Inc. 1801 Federal Street, Camden, NJ 08105 USA
Contact Information:	856-626-1550 info@resintech.com

SECTION 2: Hazard Identification	
2A: OSHA Hazard classification 0 = Negligible 1 = Slight 2 = Moderate 3 = High 4 = Extreme	Not hazardous or dangerous Health - 0 (0 = Negligible) Fire - 1 (1 = Slight) Reactivity - 0 (0 = Negligible) Special - N/A
 WARNING	(Contains ion exchange resin) (Contains granular activated carbon) H320: Causes eye irritation (Category 2B) H335: May cause respiratory irritation (Category 3)* * Chronic risk from breathing dust

SECTION 2: Hazard Identification Continued	
Precautionary Statements	<p>P261: Avoid breathing dust/fume/gas/mist/vapors/spray</p> <p>P264: Wash hands thoroughly after handling.</p> <p>P280: Wear protective gloves/protective clothing/eye protection/face protection</p> <p>P304+340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.</p> <p>P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing.</p> <p>P333+313: If skin irritation or a rash occurs: Get medical advice/attention.</p> <p>P337+313: If eye irritation persists get medical advice/attention.</p> <p>P403+233: Store in a well-ventilated place. Keep container tightly closed.</p> <p>P411: Store at temperatures not exceeding 50 °C/ 122 °F.</p>
2B: Product description	<p>SBACR - White to cream colored solid beads approximately 0.6 mm diameter with slight amine odor.</p> <p>Carbon - Black irregular pieces with little or no odor.</p>
2C: Precautions for use	Safety glasses and gloves recommended. Slipping hazard if spilled. Wet carbon adsorbs oxygen from air and can cause a hazard in confined spaces. Avoid breathing dust when handling dry carbon. Dust mask or respirator recommended for poorly ventilated spaces.
Potential health effects	Will cause eye irritation. Will cause skin irritation. Ingestion is not likely to pose a health risk.
2D: Environmental effects	This product may alter the pH of any water that

SECTION 3: Composition/ Information on Ingredients	
3A: Chemical name	<p>SBACR-MP-HP - Polyacrylic copolymer functionalized with trimethylamine</p> <p>Carbon-Granular Activated carbon</p>
3B: Ingredients: Water	<p>SBACR-MP-HP - CAS# 7440-44-0 (80 - 98%)</p> <p>Carbon - CAS# 7732-18-5 (40 - 70%)</p>
Polyacrylic copolymer functionalized with trimethylamine	CAS# 65997-24-2 (30 - 60%)
Granular Activated carbon	CAS# 7440-44-0 (80 - 98%)

Revision 1.0
 © 2020 ResinTech, Inc.



SECTION 4: First Aid Measures	
4A: Inhalation	Dust may be mildly irritating to the upper respiratory tract. No adverse effects expected- normal use of product does not produce odors or vapors.
4B: Skin	Wash with soap and water- seek medical attention if a rash develops.
4C: Eye contact	Wash immediately with water- seek attention if discomfort continues.
4D: Ingestion	No adverse effects expected for small amounts, larger amounts can cause stomach irritation. Seek medical attention if discomfort occurs.

SECTION 5: Fire Fighting Measures	
5A: Flammability	NFPA Fire rating = 1
5B: Extinguishing media	Water, CO ₂ , foam, dry powder
5C: Fire fighting Procedures	Follow general firefighting procedures indicated in the work place. Seek medical attention if discomfort continues.
5D: Protective Equipment	MSHA/NIOSH approved self-contained breathing gear, full protective clothing.
5E: Combustion Products	Carbon oxides and other toxic gasses and vapors.
5F: Unusual Hazards	Product is not combustible until moisture is removed. Resin begins to burn at approximately 230° C. Auto ignition can occur above 500° C.

SECTION 6: Accidental Release Measures	
6A: Personal Precautions	Keep people away, spilled resin can be a slipping hazard, wear gloves and safety glasses to minimize skin or eye contact.
6B: Incompatible Chemicals	Strong oxidants can create risk of combustion products similar to burning, exposure to strong bases can cause a rapid temperature increase.
6C: Environmental Precautions	Keep out of public sewers and waterways.
6D: Containment Materials	Use plastic or paper containers, unlined metal containers not recommended.
6E: Methods of Clean-up	Sweep up material and transfer to containers.

SECTION 7: Handling and Storage	
7A: Handling	Avoid prolonged skin contact. Avoid contact with salts or with salty water to prevent premature exhaustion of the resin. Keep resin moist and avoid allowing resin to completely dry.
7B: Storage	Store in a cool dry place (0° to 45° C) in the original shipping container. This product is thermally sensitive and will have reduced shelf life if subjected to extended periods of time at temperatures exceeding 50° C. Although freezing does not usually damage ion exchange resins, avoid repeated freeze thaw cycles.
7A: TSCA considerations	Ion exchange resins should be listed on the TSCA Inventory in compliance with State and Federal Regulations.

SECTION 8: Exposure Controls/Personal Protection	
8A: Personal Precautions	None noted.
8B: Incompatible Chemicals	Provide adequate ventilation.
8C: Personal Protection Measures	Eye Protection- Safety glasses or goggles. Respiratory Protection - Dust mask or respirator recommended for poorly ventilated spaces. Protective Gloves - Not required for limited exposure but recommended for extended contact.

SECTION 9: Physical and Chemical Properties	
Appearance	SBACR-MP-HP- White or cream colored beads approx. 0.6 mm diameter. Carbon- Irregular black granular pieces.
Flammability or explosive limits	SBACR-MP-HP- Flammable above 500° C Carbon- Flammable above 220° C
Odor	SBACR-MP-HP- Mild amine odor Carbon- None
Physical State	Solid
Vapor pressure	N/A
Odor threshold	N/A
Vapor density	N/A

SECTION 9: Physical and Chemical Properties	
pH	Near neutral (6 to 8 typical)
Relative density	SBACR-MP-HP- Approx 680 grams/Liter Carbon- Approx 400 grams/Liter
Melting point/freezing point	SBACR-MP-HP- Does not melt, freezes at approx. 0 C Carbon- Does not melt or freeze
Solubility	Insoluble in water and most solvents
Boiling point	Does not boil
Flash point	SBACR-MP-HP- Approx 500° C Carbon- >220° C
Evaporation rate	Does not evaporate
Partition Coefficient (n-octanol/water)	N/A
Auto-ignition temperature	SBACR-MP-HP- Approx 500° C Carbon- >220° C
Decomposition temperature	SBACR-MP-HP- Above 230° C Carbon- above 220° C
Viscosity	N/A

SECTION 10: Stability and Reactivity	
10A: Stability	Stable under normal conditions.
10B: Conditions to Avoid	Heat, exposure to strong oxidants.
10C: Hazardous by-products	Organic sulfonates, charred polystyrene, aromatic acids and hydrocarbons, organic amines, nitrogen oxides, carbon oxides, sulfur oxides, chlorinated hydrocarbons.
10D: Incompatible materials	Strong oxidizing agents (such as HNO ₃)
10E: Combustion Products	Does not occur

SECTION 11: Toxicological Information	
11A: Likely Routes of Exposure	Oral, skin or eye contact.
11B: Effects of exposure	Delayed - None known. Immediate (acute) - None known. Chronic - None known.

SECTION 11: Toxicological Information

11C: Toxicity Measures	Skin Adsorption - Unlikely, some transfer of acidity is possible. Ingestion - Oral toxicity believed to be low but no LD50 has been established. Inhalation - Unknown, vapors are very unlikely due to physical properties (insoluble solid).
11D: Toxicity Symptoms	Skin Adsorption - Mild Rash. Ingestion - Indigestion or general malaise. Inhalation - Unknown.
11E: Carcinogenicity	None known

SECTION 12: Ecological information

12A: Eco toxicity	Not acutely harmful to plant or animal life.
12B: Mobility	Insoluble, acidity or causticity may escape if wet.
12C: Biodegradability	Not biodegradable.
12D: Bioaccumulation	Insignificant.
12E: Other adverse effects	Not Harmful to the environment.

SECTION 13: Disposal Considerations

13A: General considerations	Material is non-hazardous. However, pH may be below general landfill limits.
13B: Disposal Containers	Most plastic and paper containers are suitable. Avoid the use of unlined metal containers.
13C: Disposal methods	No specific method necessary.
13D: Sewage Disposal	Not recommended
13E: Precautions for incineration	May release acids, organic amines and toxic vapors when burned.
13F: Precautions for landfills	pH of spent resin may be high or low. Resins used to remove hazardous materials may then become hazardous mixtures.

SECTION 14: Transportation Information

14A: Transportation Class	Not classified as a dangerous good for transport by land, sea, or air.
14B: TDG	Not regulated.
14C: IATA	Not regulated.
14D: DOT (49 CFR 172.101)	Not regulated.

SECTION 15: Regulatory Information

15A: CERCLA	Not regulated
15B: SARA Title III	Not regulated
15C: Clean Air act	Not regulated
15D: Clean Water Act	Not regulated
15E: TSCA	Not regulated
15F: Canadian Regulations	WHMIS - Not a controlled product TDG - Not regulated
15G: Mexican Regulations	Not Dangerous

SECTION 16: Other Information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features. Regulatory requirements are subject to change and may differ from one location to another. It is the buyer's responsibility to ensure that their activities comply with federal, state, and local laws.

16A: Date of Revision	1 January 2021
------------------------------	----------------