

ARIES CARTRIDGE SPECIFICATION SHEET

ARIES SOFTENING

PRO SERIES, SINGLE-BED, DROP-IN CARTRIDGE

GENERAL SOFTENING
HARDNESS / IRON REMOVAL

Aries softening cartridges uses ResinTech® CGS, a cation exchange softening grade resin for residential applications. Softening cartridges remove these “hard” minerals leaving the water soft and more satisfactory for household and commercial use. Sized to fit standard slimline and big blue housings.



HIGHLIGHTS

- Fits Standard Residential & Industrial Size Housing
- Oversized Cartridge for Maximum Media Fill
- Lot numbered
- Made in the USA

APPLICATIONS

- POU
- RV

MEDIA

- ResinTech® CGS (100%)

CERTIFICATIONS

- WQA Gold Seal
- California Prop. 65 Compliant

SPECIFICATIONS

- Nominal Rating of 25µ
- Max Pressure of 125 psi (861.85 kpa)
- Max Temperature 100°F (37.8 °C)

DIMENSIONS	SERVICE FLOW	MAX FLOW	CAPACITY	PART NUMBER
2.5 x 10 in. (Slim Line)	.15 gpm (.57 lpm)	.30 gpm (1.14 lpm)	1,414 grains	AF-10-3003
2.5 x 20 in. (Slim Line)	.30 gpm (1.14 lpm)	.60 gpm (2.27 lpm)	2,520 grains	AF-20-3003
4.5 x 10 in. (Super Blue)	.30 gpm (1.14 lpm)	.60 gpm (2.27 lpm)	2,858 grains	AF-10-3003-BB
4.5 x 20 in. (Super Blue)	.75 gpm (2.84 lpm)	1.5 gpm (5.68 lpm)	6,295 grains	AF-20-3003-BB



COMPONENT

Filter cartridge Certified to NSF/ANSI Standard 42 and NSF/ANSI Standard 61 for material requirement(s) only. Filter cartridge Certified to NSF/ANSI Standard 372 for low lead compliance.

Revision 1.0

© 2020 ResinTech, Inc.

