# **SOLVENTS & ORGANICS**

PRO SERIES, SINGLE-BED, DROP-IN CARTRIDGE

SOLVENTS REMOVAL ORGANICS REMOVAL

Aries Drop-In Cartridge containing ResinTech AGC-40-CS-MG, a specially formulated granular activated carbon for use in medical applications, such as water purification for hemodialysis where the removal of free chlorine and chloramine are of prime importance.

• Resintech® AGC-40-CS-MG

• Fits Standard Residential & Industrial Size

• Oversized Cartridge for Maximum Media Fill

## **APPLICATIONS**

- Drinking Water POU
- Light Commercial
- Light Industrial

#### **MEDIA**

• ResinTech® AGC-40-CS-MG (100%)

## **CERTIFICATIONS**

- WQA Gold Seal
- California Prop. 65 Compliant

### **SPECIFICATIONS**

- Nominal Rating of 25µ
- Max Pressure of 125 psi (861.85 kpa)
- Max Temperature 100°F (37.8 °C)

		=
		1
		0000
		0000
		0000
		0000
		0000
		0000
		5000
		5000
	<	B888
	(0	8888
	U	RXXX
		$\rightarrow \rightarrow \rightarrow$
		$\times\!\!\times\!\!\times$
	7	$\mapsto \mapsto$
	$\leq$	$\times\times\times$
	3111	RXXX
		222
		222
	1	222
	2	2000
	~>	222
		2000
		DOO
	ALIL	0000
		0000
		0000
		0000
		0000

Lot numberedMade in the USA

**HIGHLIGHTS** 

Housing

DIMENSIONS	SERVICE FLOW	MAX FLOW	CAPACITY	PART NUMBER
2.5 x 10 in. (Slim Line)	.50 gpm (1.89 lpm)	1.0 gpm (3.79 lpm)	-	AF-10-1100
2.5 x 20 in. (Slim Line)	.75 gpm (2.84 lpm)	1.5 gpm (5.68 lpm)	-	AF-20-1100
4.5 x 10 in. (Super Blue)	.75 gpm (2.84 lpm)	1.5 gpm (5.68 lpm)	-	AF-10-1100-BB
4.5 x 20 in. (Super Blue)	1.0 gpm (3.79 lpm)	3.0 gpm (11.36 lpm)	-	AF-20-1100-BB



#### COMPONENT

Filter cartridge Certified to NSF/ANSI Standard 42 and NSF/ANSI Standard 61 for material requirement(s) only. Filter cartridge Certified to NSF/ANSI Standard 372 for low lead compliance.

Revision 1.0 © 2020 ResinTech, Inc.

