# **TASTE & ODOR CONTROL**

INLINE SERIES, SINGLE-BED, DROP-IN CARTRIDGE

TASTE & ODOR CORRECTION
CHLORINE REMOVAL
ORGANICS REMOVAL

Carbon filtration is an inexpensive and effective way to remove chemicals and contaminants commonly found in tap water. Aries Inline Acid Washed Carbon filters cartridges are designed for low-flow, point-of-use filtration to remove specific contaminants for a number of specialty drinking water, taste improvement and odor elimination applications.



## **HIGHLIGHTS**

- Taste, Odor & Chlorine Removal
- Prop 65 Compliant for Drinking Water Applications
- Fits Standard Residential & Industrial Housings
- Optimum Mesh Size for More Surface Area
   & Greater Adsorption
- Acid Washed Ensures a Neutral pH
- Up To 50% Higher Capacity for Longer Life
- Lot Numbered Made in the USA

### **APPLICATIONS**

- Pre and Post RO
- Water Coolers
- Ionizers
- Food and Bev
- Ice machines

#### **MEDIA**

• ResinTech® AGC-50-CS-AW (100%)

#### **CERTIFICATIONS**

- WQA Gold Seal
- California Prop. 65 Compliant

#### **SPECIFICATIONS**

- Nominal Rating of 25µ
- Max Pressure of 125 psi (861.85 kpa)
- Max Temperature 100°F (37.8 °C)

DIMENSIONS	SERVICE FLOW	MAX FLOW	CAPACTIY	PART NUMBER
6 x 2 in. (Quick Connect)	.25 gpm (.95 lpm)	.50 gpm (1.89 lpm)	1120 gallons (4,240 liters)	IFB-06-1052-QC
12 x 2 in. (Quick Connect)	.50 gpm (1.89 lpm)	1.0 gpm (3.79 lpm)	2240 gallons (8,479 liters)	IFB-12-1052-QC
6 x 2 in. (1/4 in. FNPT)	.25 gpm (.95 lpm)	.50 gpm (1.89 lpm)	1120 gallons (4,240 liters)	IFB-06-1052-FT
12 x 2 in. (1/4 in. FNPT)	.50 gpm (1.89 lpm)	1.0 gpm (3.79 lpm)	2240 gallons (8,479 liters)	IFB-12-1052-FT



#### COMPONENT

Filter cartridge Certified to NSF/ANSI Standard 42 and NSF/ANSI Standard 61 for material requirement(s) only. Filter cartridge Certified to NSF/ANSI Standard 372 for low lead compliance.

Revision 1.0 © 2020 ResinTech, Inc.

