

MAGNA SBG1P-OH-LTOC

STRONG BASE ANION

**LOW TOC GRADE
TYPE I ANION
POLYSTYRENIC POROUS GEL
HYDROXIDE FORM**

ResinTech SBG1P-OH-LTOC is a type 1 porous gel strong base anion resin in hydroxide form. The LTOC grade means it has been functionally tested to produce > 18 megohm resistivity and under 10 ppb of TOC (when paired in a mixed bed with LTOC grade cation). SBG1P-OH-LTOC is intended for use in industrial demineralizing applications such as two beds and mixed beds where a resin that has been tested to confirm high resistivity and low TOC is required.

APPLICATIONS

- Demineralization
- Anion Component in Mixed Beds

TYPICAL PROPERTIES & PHYSICAL CHARACTERISTICS

Polymer Matrix	Styrenic Porous Gel
Ionic Form	Hydroxide
Functional Group	Trimethylamine
Physical Form	Spherical Beads
Particle Size	16 to 50 US Mesh (297 - 1190 µm)
% < 50 mesh (300µm)	< 1%
Minimum Sphericity	93%
Uniformity Coefficient	1.6
Reversible Swelling	OH to Cl -20% to -28%
Temp Limit	140°F (60°C)
Capacity (meq/mL)	1.05
Shipping Weight	41 - 43 lbs/ft ³ (657 - 689 g/L)
Color	Yellow to Orange
Regenerability	Yes

PACKAGING OPTIONS

- 1 ft³ bags
- 1 ft³ boxes
- 1 ft³ drums
- 7 ft³ drums
- 42 ft³ supersacks

Revision 1.1
ResinTech, Inc.®

